

1

2

3

4

5

6

Click for More  
information

DS-2CD1323G0-I

DS-2CD1123G0-I

DS-2CD1143G0-I

DS-2CD2120F-IS

DS-2CD2123G0-IS

DS-2CD2143G0-IS

**hik24**  
Electronic Design



Price (Rials)

1۷,۰۷۰,۰۰۰

1۸,۰۳۰,۰۰۰

۲۴,۲۴۰,۰۰۰

۲۵,۳۰۰,۰۰۰

۲۸,۳۷۰,۰۰۰

۳۰,۷۴۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/20fps)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2688x1520/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2

0.028Lux @ F2

0.01Lux @ F2

0.01 Lux @ F1.2

0.01 Lux @ F1.2

Lens

2.8/4/6mm Fix

2.8mm Fix

2.8mm Fix

2.8mm Fix

2.8mm Fix

2.8mm Fix

Viewing Angle

98.5°/79°/51

98.5°

98.5°

98.5°

98.5°

98.5°

IR Range

Up to 30m

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m

Up to 30m

Body Type &amp; Standard

Metal / IP67

Plastic / IP67&amp; IK10

Plastic / IP67 &amp; IK10

Metal / IP66 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

SD Card Support

No

No

No

Yes (Upto 128 G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

No

No

No

Yes( 1ch. Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

DWDR

DWDR

DWDR

DWDR

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, H.264+  
COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP

7

8

9

10

11

12

Click for More  
information

DS-2CD2152F-IS

DS-2CD2163G0-IS

DS-2CD2183G0-IS

DS-2CD2523G0-IS

DS-2CD2542FWD-IS

DS-2CD2543G0-IS

**hik24**  
Electronic Design



Price (Rials)

۳۱,۰۸۱,۰۰۰

۳۶,۶۵۰,۰۰۰

۴۳,۱۵۰,۰۰۰

Call:

Call:

Call:

Camera Type

Dome

Dome

Dome

Mini Dome

Mini Dome

Mini Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.5" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

5MP(2560×1920/20fps)

6MP(3072×2048/20fps)

8MP(3840×2160/15fps)

2MP(1920×1080/25FPS)

4MP(2688×1520/20fps)

4MP(2688×1520/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F2

0.028 Lux @ F2

0.028 Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

4/6mm Fix

2.8mm Fix

2.8mm Fix

4 mm Fix

2.8/4 mm Fix

2.8/4/6mm Fix

Viewing Angle

79/51°

98.5°

98.5°

79°

79°

98.5°/79°/51

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 10m

Up to 10m

Up to 10m (EXIR)

Body Type &amp; Standard

Metal / IP67&amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP66

Metal / IP66 &amp; IK08

Metal / IP67

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

Yes

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.264+  
COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, H.264+  
COMP3D DNR, BLC, ROI, H.264+  
COMP

13

16

14

15

17

18

Click for More  
information

DS-2CD2563G0-IS

DS-2CD2720F-I

DS-2CD1723G0-I

DS-2CD1743G0-I

DS-2CD2720F-IZ

DS-2CD2743G0-  
IZS

**hik24**  
Electronic Design



Price (Rials)

Call:

۳۰,۵۱۲,۰۰۰

۳۳,۸۲۶,۰۰۰

۳۷,۲۴۰,۰۰۰

۳۷,۹۵۰,۰۰۰

۶۱,۲۳۹,۰۰۰

Camera Type

Mini Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

6MP(3072 × 2048/20fps)

2MP(1920x1080/25FPS)

2MP(1920x1080/30FPS)

4MP (2560x1440/20FPS)

2MP (1920x1080/25FPS)

4MP (2688x1520/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.018Lux @ F2

0.01Lux @ F1.2

0.01Lux @ F2

Lens

2.8/4/6mm Fix

2.8-12mm Varifocal

2.8-12mm Varifocal

2.8-12mm Varifocal

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

98.5°/79°/51

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 10m

Up to 30m

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m (EXIR)

Body Type &amp; Standard

Metal&amp;Plastic / IP67

Metal / IP66 &amp; IK10

Metal/ IP67 &amp; IK10

Metal / IP67

Metal / IP66 &amp; IK10

Metal/ IP67 &amp; IK10

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

Yes (1.ch Audio Input)

No

No

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

DWDR

DWDR

Yes (120db)

DWDR

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, H.264+  
COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, H.264  
COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP

19

20

21

22

23

Click for More  
information

DS-2CD2423G0-IW

DS-2CD2442FWD-IW

DS-2CD2443G0-IW

DS-2CD2322WD-I

**hik24**  
Electronic Design



Price (Rials)

Call:

۲۳,۶۵۰,۰۰۰

Call:

۲۹,۲۶۰,۰۰۰

۲۶,۳۷۵,۰۰۰

Camera Type

Cube

Cube

Cube

Cube

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

2MP (1920x1080/30FPS)

4MP(2560x1440/20fps)

4MP(2560x1440/20fps)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8mm Fix

2.8mm/4mm Fix

2.8mm Fix

2.8mm/4mm Fix

2.8/4/6mm Fix

Viewing Angle

98.5°

98.5°/79°

98.5°

98.5°/79°

98.5°/79°/51

IR Range

Up to 10m

Up to 10m

Up to 10m

Up to 10m

Up to 30m (EXIR)

Body Type &amp; Standard

Plastic

Plastic

Plastic

Plastic

Plastic / IP67

SD Card Support

Yes (up to 128GB)

Yes (up to 128GB)

Yes (up to 128GB)

Yes (up to 128GB)

No

Microphone Support

Yes (Build-in Mic &amp; Spkr)

Yes (Build-in Mic &amp; Spkr)

Yes (Build-in Mic &amp; Spkr)

-

No

WDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

Yes

Yes

Yes

No

No

Power Supply

12V DC

12V DC

12V DC

12V DC

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.264  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.264+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.264+  
COMP

24

25

26

27

28

29

Click for More  
information

DS-2CD1023G0-I

DS-2CD1043G0-I

DS-2CD1053G0-I

DS-2CD2023G0-I

DS-2CD2043G0-I

DS-2CD2052-I

**hik24**  
Electronic Design



Price (Rials)

۱۶,۸۵۰,۰۰۰

۲۳,۰۵۰,۰۰۰

۲۵,۰۴۷,۰۰۰

۲۶,۳۰۰,۰۰۰

۳۰,۰۴۰,۰۰۰

۲۹,۵۳۸,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

4MP(2560x1440/20fps)

5MP(2560x1920/)

2MP(1920x1080/30FPS)

4MP(2560x1440/30fps)

5MP(2560x1920/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.028Lux @ F2

0.01 Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8mm Fix

2.8mmFix

2.8/4/6mm Fix

2.8/4/6/8mm Fix

2.8mm Fix

4mm Fix

Viewing Angle

98.5°

98.5°

98.5°/79°/54

98.5°/79°/54/43

98.5°

79°

IR Range

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type &amp; Standard

Plastic / IP67

Plastic / IP67

Plastic / IP67

Metal / IP67

Metal / IP67

Metal / IP66

SD Card Support

No

No

No

Yes (Up to 128 G)

Yes (Up to 128 G)

No

Microphone Support

No

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

Yes (120db)

Yes (120db)

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP,PIR

3D DNR, BLC, VCA,

3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.264+  
COMP

30

31

32

33

34

35

Click for More  
information

DS-2CD2063G0-I

DS-2CD2083G0-I

DS-2CD2T43G0-I5

DS-2CD2T63G0-I5

DS-2CD2T63G0-I8

**hik24**  
Electronic Design



Price (Rials)	Call:	Call:	Call:	۳۳,۵۱۰,۰۰۰	۳۸,۵۸۲,۰۰۰	۴۰,۷۸۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.9" Prog. CMOS	1/2.5" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.9" Prog. CMOS	1/2.9" Prog. CMOS
Resolution	6MP(3072×2048/20fps)	8MP(3840×2160/15fps)	3MP(2048×1536)	4MP(2688×1520/25fps)	6MP(3072×2048/20fps)	6MP(3072×2048/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.028Lux @ F2	0.005Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8mm Fix	2.8mm Fix	2.8/4/6mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix
Viewing Angle	98.5°	98.5°	98.5°/79°/51	98.5°/79°	98.5°/79°	98.5°/79°
IR Range	Up to 30m	Up to 30m	Up to 80m	Up to 50m (EXIR)	Up to 50m (EXIR)	Up to 80m (EXIR)
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 128 G)	Yes (Up to 128 G)	Yes (Up to 128G)	Yes (Up to 128G)	Yes (Up to 128G)	Yes (Up to 128G)
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	No	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR

36

37

38

39

40

41

Click for More  
information

DS-2CD1623G0-I

DS-2CD1623G0-IZ

DS-2CD1643G0-I

DS-2CD2632F-I

DS-2CD2T83G0-I5

DS-2CD2T83G0-I8

**hik24**  
Electronic Design



Price (Rials)	۳۴,۳۸۳,۰۰۰	۳۸,۴۲۰,۰۰۰	۴۱,۳۸۰,۰۰۰	۴۰,۱۹۰,۰۰۰	Call:	۴۸,۴۷۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.5" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	2MP(1920×1080/30fps)	2MP(1920×1080/30fps)	4MP(2560×1440/20fps)	3MP(2048×1536/25FPS)	8MP(3840×2160/15fps)	8MP(3840×2160/15fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.005Lux @ F1.2	0.028Lux @ F2	0.028Lux @ F2
Lens	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8mm/4mm Fix	2.8mm/4mm Fix
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	98.5°/79°	98.5°/79°
IR Range	Up to 30m	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 50m (EXIR)	Up to 80m (EXIR)
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP66	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 128 G)	Yes (Up to 128 G)	Yes (Up to 128 G)	Yes (Up to 128G)	Yes (Up to 128G)	Yes (Up to 128G)
Microphone Support	No	No	No	No	No	No
WDR	DWDR	DWDR	Yes (120db)	DWDR	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI	3D DNR, BLC, ROI	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR

Click for More  
information

DS-2CD2643G0-IZS

**hik24**  
Electronic Design



© 2019 Hikvision

Price (Rials)	٦٢,٠٦٠,٠٠٠
Camera Type	Bullet
Imaging Sensor	1/3" Prog. CMOS
Resolution	4MP(2688×1520/25fps)
Network Standard	ONVIF
Min. Illustration	0.018Lux @ F1.6
Lens	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°
IR Range	Up to 50m
Body Type & Standard	Metal / IP67 & IK10
SD Card Support	Yes (Up to 128 G)
Microphone Support	Yes (1.ch Audio Input)
WDR	Yes (120db)
WIFI	No
Power Supply	12V DC or POE
Other Feathures	3D DNR, BLC, VCA, H.265+ COMP



43

44

45

46

Click for More  
information

DS-2CV2U21FD-IW

DS-2CD2Q10FD-IW

DS-2CV2Q21FD-IW

DS-2CD2955FWD-IS

**hik24**  
Electronic Design



Price (Rials)

١٤,٢٧٠,٠٠٠

٢٠,٨٠٠,٠٠٠

Call:

٧٤,٥٠,٠٠٠

Camera Type

Cube

Indoor Pan-tilt

Indoor Pan-tilt

FishEye

Imaging Sensor

1/2.8" Prog. CMOS

1/4" Prog. CMOS

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

2MP (1920x1080/30FPS)

1MP (1280x720/30FPS)

2MP (1920x1080/30FPS)

5MP(2560x1920/30FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8mm Fix

4mm Fix

2.8mm Fix

1.05 mm

Viewing Angle

98.5°

79°

98.5°

186° Panoramic

IR Range

Up to 10m

Up to 10m

Up to 5m

Up to 8m

Body Type &amp; Standard

Plastic

Plastic

Plastic

-

SD Card Support

Yes (up to 128GB)

Yes (up to 128GB)

Yes (up to 128GB)

Yes (up to 128GB)

Microphone Support

Yes (Build-in Mic &amp; Spkr)

Yes (Build-in Mic &amp; Spkr)

Yes (Build-in Mic &amp; Spkr)

Yes (1.ch Audio Input)

WDR

DWDR

DWDR

DWDR

Yes (120db)

WIFI

Built in WIFI

Yes ( Built in WIFI)

Yes ( Built in WIFI)

No

Power Supply

12V DC

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,  
H.264 COMPMotorizedPan-Tilt  
Rotation,PIR,3DDNR,  
BLC,ROI,VCA3D DNR, BLC, ROI, VCA,  
H.264 COMP3D DNR, BLC, ROI, VCA, HLC,  
H.265+ COMP

47

48

49

50

51

52

Click for More  
information

DS-2PT3326IZ-DE3

DS-2DE4225IW-DE

DS-2DE5230W-AE

DS-2DE7184-AE

**hik24**  
Electronic Design



Price (Rials)

۳۷,۳۱۷,۰۰۰

۱۰۸,۱۰۰,۰۰۰

۱۰۶,۱۰۸,۰۰۰

۱۶۹,۵۱۰,۰۰۰

Call:

۱۱۰,۶۱۱,۰۰۰

Camera Type

Pan-Tilt Dome

Mini PTZ/Panoramic

PTZ

PTZ

PTZ

PTZ

Imaging Sensor

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

5Mp(2560×1920/20fps)

2MP(1920×1080/30FPS)

2MP(1920×1080/30FPS)

2MP(1920×1080/30FPS)

2MP(1920×1080/30FPS)

2MP(1920×1080/30FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux/F1.6

0.005Lux/F1.6

0.02Lux/F1/5

0.01Lux/F1.6

0.01Lux/F1.6

Lens

2.8/4/6mm Fix

2.8-12mm

-

4.7-94mm Motorized

4.3-129mm Motorized

4.7-94mm Motorized

Optical Zoom

98.5°/79°/51

4x

25x

20x

30x

20x

IR Range

Up to 10m

10m

100m

150m

-

100m

Body Type

Metal / IP67

Aluminum alloy

Metal

Metal

Metal

-

IP Standard

Yes (up to 128GB)

IP66

-

IP66

IP66 &amp; IK10

IP66

WDR

Yes (1.ch Audio Input)

DWDR

Yes (120db)

DWDR

DWDR

DWDR

WIFI

DWDR

No

No

No

No

No

Power Supply

No

12VDC &amp; POE(802.3at)

12VDC &amp; POE(802.3at)

24v AC &amp; HI-POE

AC24V &amp; POE(802.3at)

24VDC &amp; POE(802.3at)

Other Features

Motorized Pan-Tilt  
Rotation, 3DDNR, BLC, ROI

8x Digital Zoom, ICR, VCA,  
Micro SD Up to 256G, HLC

16x Digital Zoom, 3DDNR,  
ICR, BLC, , Micro SD Upto  
256G,

16x Digital Zoom, H.265+,  
3DDNR, ICR, BLC, , Micro SD  
Upto 128G, 1ch.audio

16x Digital Zoom, MICROSD,  
3D DNR, H.264, BLC, , Micro  
SD Upto 128G, 1ch.audio

16x Digital Zoom, VCA,  
Micro SD Up to 32G

Click for More  
information

DS-2DE7232IW-AE

**hik24**  
Electronic Design



Price (Rials)

۱۶۸,۸۷۲,۰۰۰

Camera Type

PTZ

Imaging Sensor

1/2.8" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

Network Standard

ONVIF

Min. Illustration

0.005Lux/F1.6

Lens

4.7-94mm Motorized

Optical Zoom

32x

IR Range

150m

Body Type

-

IP Standard

IP66

WDR

Yes (120db)

WIFI

No

Power Supply

24VAC & POE(802.3at)

Other Features

16x Digital Zoom, VCA,  
Micro SD Up to 256G

54

55

56

57

58

59

Click for More  
information

DS-7104NI-Q1/M

DS-7104NI-Q1/4PM

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7604NI-Q1

DS-7604NI-Q1/4P

**hik24**  
Electronic Design



Price (Rials)

۱۳,۸۲۰,۰۰۰

۲۲,۸۳۰,۰۰۰

Call:

Call:

۲۱,۲۳۸,۰۰۰

۳۰,۴۸۶,۰۰۰

NVR Type

4 Ch

4 Ch POE NVR

4 Ch NVR

4 Ch POE NVR

4 Ch NVR

4 Ch POE NVR

Input BandWidth

40Mbps

40Mbps

40Mbps

40Mbps

40Mbps

40Mbps

Output Bandwidth

60Mbps

60Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA

POE Ports

-

4 POE Ports

-

4 POE Ports

-

4 POE Ports

SATA Interface

1 HDD up to 6TB

1 HDD up to 6TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Feathures

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR

60

61

62

63

64

65

Click for More  
information

DS-7108NI-Q1/M

DS-7608NI-Q1

DS-7608NI-K1

DS-7608NI-E2

DS-7108NI-Q1/8P/M

DS-7608NI-K2/8P

**hik24**  
Electronic Design



Price (Rials)

1۷,۳۷۰,۰۰۰

۲۵,۷۰۰,۰۰۰

۲۶,۴۳۰,۰۰۰

۳۰,۹۹۲,۰۰۰

۳۳,۱۹۰,۰۰۰

Call:

NVR Type

8 Ch NVR

8 Ch NVR

8 Ch NVR

8 Ch NVR

8 Ch NVR

8 Ch POE NVR

Input BandWidth

60Mbps

80Mbps

60Mbps

80Mbps

60Mbps

80Mbps

Output Bandwidth

60Mbps

80Mbps

80Mbps

80Mbps

60Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 5Mp

Upto 4Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 1080P  
1 Port VGA : 1080P1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

-

-

-

8 POE Ports

8 POE Ports

SATA Interface

1 HDD up to 6TB

1 HDD up to 10TB

1 HDD up to 6TB

2 HDD up to 10TB

1 HDD up to 6TB

2 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Feathures

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR  
Alarm I/O 4/1H.264+ COMPR  
Alarm I/O 4/1

H.265+ COMPR

H.265+ COMPR  
Alarm I/O 4/1

66

67

Click for More  
information

DS-7608NI-Q2

DS-7608NI-Q1/8P

**hik24**  
Electronic Design



Logo Member

Price (Rials)	Call:	Call:
NVR Type	8 Ch NVR	8 Ch POE NVR
Input BandWidth	80Mbps	80Mbps
Output Bandwidth	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 4k 1 Port VGA : 1920p	1 Port HDMI : 4k 1 Port VGA
POE Ports	-	8 POE Ports
SATA Interface	2 HDD up to 10TB	1 HDD up to 10TB
Network Interface	1 RJ45 1000M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U
Other Features	H.265+ COMPR	H.265+ COMPR

68

69

70

71

72

73

Click for More  
information

DS-7716NI-E4

DS-7716NI-E4/16P

DS-7616NI-K2

DS-7616NI-Q1

DS-7616NI-Q2

DS-7716NI-Q4

**hik24**  
Electronic Design



Price (Rials)

Call:

Call:

Call:

۳۱,۱۰,۰۰۰

۳۲,۴۴,۰۰۰

۶۹,۳۸,۰۰۰

NVR Type

16 Ch NVR

16 Ch NVR

16 Ch NVR

16 Ch NVR

16 Ch NVR

16 Ch NVR

Input BandWidth

160Mbps

160Mbps

160Mbps

160Mbps

160Mbps

160Mbps

Output Bandwidth

80Mbps

80Mbps

160Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 5Mp

Upto 5Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

16 POE Ports

-

-

-

-

SATA Interface

4 HDD up to 10TB

4 HDD up to 10TB

2 HDD up to 10TB

1 HDD up to 10TB

2 HDD up to 6TB

4 HDD up to 6TB

Network Interface

2 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

19" 1.5 Case

19" 1.5 Case

Standalone 1U

1U chassis

Standalone 1U

Standalone 1U

Other Features

H.264+ COMPR  
Alarm I/O 4/1H.264+ COMPR  
Alarm I/O 4/1H.265+ COMPR  
Alarm I/O 4/1

H.265+ COMPR

H.265+ COMPR  
Alarm I/O 4/1H.265+ COMPR  
Alarm I/O 4/1

74

75

76

77

Click for More  
information

DS-7616NI-K2/16P

DS-7716NI-K4

DS-7716NI-K4/16P

**hik24**  
Electronic Design



Price (Rials)

Call:

٤٤,٧٠,٠٠٠

٧٧,٤١٨,٠٠٠

Call:

NVR Type

16 Ch NVR

16 Ch NVR

16 Ch NVR

16 Ch NVR

Input BandWidth

160Mbps

160Mbps

160Mbps

160Mbps

Output Bandwidth

160Mbps

80Mbps

160Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4k  
1 Port VGA : 1920P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

16 POE Ports

16 POE Ports

-

16 POE Ports

SATA Interface

2 HDD up to 10TB

2 HDD up to 10TB

4 HDD up to 10TB

4 HDD up to 10TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

1U chassis

19" 1.5 Case

19" 1.5 Case

Other Features

H.265+ COMPR  
Alarm I/O 4/1

H.265+ COMPR

H.265+ COMPR  
Alarm I/O 4/1H.265+ COMPR  
Alarm I/O 4/1



78

79

80

81

82

83

Click for More  
information

DS-7732NI-E4

DS-7732NI-Q4

DS-7732NI-E4/16P DS-7732NI-Q4/16P DS-7732NI-K4/16P

**hik24**  
Electronic Design



Price (Rials)

Call:

٨٥,٥٩٠,٠٠٠

١٠٢,٣٨٠,٠٠٠

١٢٠,١٧٥,٠٠٠

١٢٤,٠٣٠,٠٠٠

Call:

NVR Type

32 Ch NVR

32 Ch NVR

32 Ch NVR

32 Ch NVR

32 Ch NVR

32 Ch POE NVR

Input BandWidth

160Mbps

200Mbps

256Mbps

160Mbps

200Mbps

256Mbps

Output Bandwidth

80Mbps

128Mbps

160Mbps

80Mbps

128Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 5Mp

Upto 8Mp

Upto 8Mp

Upto 5Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

-

-

16 POE Ports

16 POE Ports

16 POE Ports

SATA Interface

4 HDD up to 10TB

4 HDD up to 6TB

4 HDD up to 10TB

4 HDD up to 10TB

4 HDD up to 6TB

4 HDD up to 10TB

Network Interface

2 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

19" 1.5 Case

19" Case

19" 1.5 Case

19" 1.5 Case

19" Case

19" 1.5 Case

Other Features

1 E-SATA Port  
H.264+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/41 E-SATA Port  
H.264+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4

Click for More  
information

DS-7600NI-E1/A

**hik24**  
Electronic Design



Logo HeliStar

Price (Rials)

۱۲۵,۴۸۸,۰۰۰

NVR Type

Input BandWidth

Output Bandwidth

Audio Input/Output

Decoding Capacity

Video Output

POE Ports

SATA Interface

Network Interface

Chassis

Other Feathures

Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed